

Technical Specifications Reader Mounting Bracket

Description

The Reader Mounting Bracket is used to flush mount Elpas LF Exciters or Location Readers in suspended ceiling tiles.

The bracket is constructed of coated steel and has a 15mm/0.59inch center hole to allow cables to pass through. The bracket also contains two 4mm/0.16inch diameter threaded holes; (83mm/3.26 inches apart) for clamping the base of the device into place, plus two 5mm/0.2 inch holes at each end of the bracket for fixing the bracket to the ceiling tile.

Two M4 x 35mm Phillips head screws are included per bracket.

Ordering Information

Part Number	Description
5-RDT09100	Reader Mounting Bracket (5 units)


Compatible Elpas IR/RF Readers and LF Exciters


Part No. Series	Description
5-RDT00001	Location Readers, IR
5-RDF00001	Location Readers, RF
5-RDF00433-5	Two-piece Location Readers, RF
5-RLE00125B/W	LF Exciters, All Configurations




Mounting Information

- 1. Cut a 123mm (4.8 inch) diameter hole n the tile where the device is to be flush mounted.
- 2. Pull the applicable cable(s) through the cable entry hole of the bracket and into the base of the reader or exciter.
- Insert the bracket through the mounting hole placing it on top of the ceiling tile. Position it so that the bracket is firmly supported by the ceiling tile.
- 4. Insert the base of the reader/ exciter into the mounting hole. Next, screw the base to the mounting bracket place using the 2 supplied M4 x 35mm Philips head screws. Ensure that the screw heads are recessed inside the screw holes. If not the device will not close properly and damage may occur.
- Connect the cable(s) to the reader/exciter; then insert the device back into its base.







Office Locations

VT World Headquarters Tel Aviv, Israel Tel: +972-3-7681400 marketing@visonictech.com

VT Americas Bloomfield, CT (USA) Tel: 800-223-0020 vta_marketing@visonictech.com

VT United Kingdom Beckenham Kent BR3 9BF, UK Tel: +44-870-730-0840 vtuk_marketing@visonictech.com

Visonic GmbH D-40215 Düsseldorf, Germany Tel: +49-(0)-221-600-696-0 support@visonictech.de

About Visonic Technologies

Visonic Technologies, a fully owned subsidiary of Visonic, Ltd. (VSC.L) is a global leader in enterprise-class, active and passive RFID/ RTLS real-time visibility solutions. Distributed under the Elpas, SpiderAlert, VisAccess and EIRIS system names the company's products deliver personnel identification and safety; supply-chain logistics, asset protection and facility supervision.



Contact: marketing@visonictech.com Visit: <u>www.visonictech.com</u> Elpas Surface Mounting Bracket-Technical Specifications V2.0 - Sept. 07