

MODEL: R4K4020 — LCD CONSOLE



R4K4020



R4KRECP



FEATURES

- Over 250 possible unique facility-defined call priorities
- Twenty-four (24) programmable functions
- 4-line display with associated function/scroll/select buttons
- Day/Night tones
- Optional tone mute of calls in progress
- Displays up to three (3) incoming calls with the ability to scroll to see additional pending calls
- Six (6) unique call-in tones
- Choice of instant 2-way communication with handset or push-to-talk operation via speaker-microphone
- Room swing capabilities
- Continuously supervised with self-diagnosing error messages

SPECIFICATIONS

Display: 4-line by 20 characters (80 characters total)
alpha-numeric backlit LCD

Power Requirements: 15.5 V DC @ 0.375 A

Connection: K-bus connection

Weight: 2.25 lb. (1.02 kg)

Size: W: 10.09" (21.74 cm)
H: 8.56" (25.63 cm)
D: 2.84" (7.21 cm)

Housing & Finish: Lexan® protective display cover. High impact flame retardant Cyloloy® equivalent to GE Cyloloy 71705 plastic in ghost grey.

Controls: Three (3) soft touch keys programmable for up to twenty-four (24) functions
Three (3) line selectors
One (1) scroll key pad for call selection
One (1) scroll key pad for function selection
One (1) standard dial pad
One (1) Push-to-Talk button
One (1) Cancel button
One (1) hookswitch
One (1) K-bus DIP switch address (RJ-45)

Terminations: Connecting cable and receptacle supplied

Console Backbox Options: Steel City 58371 3/4R, Raco 561,
or any other single gang backbox

Certification: UL/C-UL 1069; CE;
FCC Part 15 Class A

*Architect and Engineer (A&E) Specifications available online at: customerconnection.rauland.com
Specifications subject to change without notice*

©Copyright 2014 Rauland-Borg Corporation Printed in USA Rev 04/2014

USA-Mt.Prospect, IL
Canada
www.rauland.com

• 800-752-7725
• 905-607-2335

• Fax 800-217-0977
• Fax 905-607-3554



Rauland-Borg Corporation