

MODEL: R4KSLC1 — SINGLE LIGHTING CONTROL MODULE



R4KSLC1



FEATURES



- Provides 4 low-voltage outputs for connection to high-voltage lighting controller
- Pigtail wire connector for easy installation
- Protective shrink-wrapped cover for location in quad wiring boxes

SPECIFICATIONS

Power Required: 15.5V @ 13mA

Contact Ratings:

Size: W: 1.88" (4.78 cm)

H: 3.00" (7.62 cm)

D: 0.50" (1.27 cm)

Controls: 4 Normally Open Active Outputs

Terminations: Pre-wired pigtail, plug-on connector

Certification: UL/C-UL 1069; CE.

DESCRIPTION



The R4KSLC1 – Single Lighting Control Module provides total Pillow Speaker isolation for lighting relays (auxiliary device which is non-UL 1069 listed). The R4KSLC1 is associated with the R4K13VA Audio Enhanced Patient Station, R4K16LV Single Enhanced Patient Station - Non Speech, and R4K17V Single Enhanced Patient Station. The module provides a pre-wired pigtails output (low-voltage) to interface with lighting relays on a controller to

switch high-voltage on lights.

An R4KSLC1 is required for all Pillow Speakers with lighting control (remote device interface) except when the Pillow Speaker is only interfaced to a UL listed hospital grade television and no other devices.

ASSOCIATED EQUIPMENT

R4K13VA — Audio Single Patient Station

R4K16LV — Single Enhanced Patient Station - Non Speech

R4K17V — Single Enhanced Patient Station

Pillow Speakers

NCLV120/NCLV240 — High Voltage Light Switch Controller

CCDIN3 - Call Cord

*Architect and Engineer (A&E) Specifications available online at: customerconnection.rauland.com
Specifications subject to change without notice*

©Copyright 2014 Rauland-Borg Corporation Printed in USA Rev 04/2014

USA-Mt.Prospect, IL
Canada
www.rauland.com

• 800-752-7725
• 905-607-2335

• Fax 800-217-0977
• Fax 905-607-3554



Rauland-Borg Corporation