# Responder® Health Care Communications Systems

## MODEL: R4KPB11 — PUSH FOR HELP STATION





### R4KPB11

#### **F**EATURES

- Call-Assurance LED
- · Extra large, back-lit pushbutton for easy activation
- · Cancel touchpoint
- · Continuous supervision for station presence
- Unique mounting plate design accommodates a variety of single and dual gang backboxes
- · Plug-in connectors for easy service



### **S**PECIFICATIONS

Power Required: 15.5V DC @ 4mA

Weight: 0.25 lb. (0.11 kg)
Size: W: 4.21" (10.69 cm)
H: 5.46" (13.87 cm)
D: 1.17" (2.97 cm)

Housing & Finish: High-impact molded ABS94VO;

light gray faceplate

Controls: One (1) Call touchpoint One (1) Cancel button

One (1) Call-Assurance indicator

Terminations: Plug-on connectors

Backbox Options: Raco 561, Steel City 58371 3/4R or any

other single gang backbox. Mounting plate allows for North American, South American, and European style single

and dual gang backboxes

Certification: UL/C-UL 1069; CE.

The Push For Help station is connected to its associated corridor light or domeless room controller and is continually supervised for station presence. Through programming, a "Trouble" message can annunciate at the associated console(s) when the station is removed from the system.

DCA200 / DCA216 — Audio Domeless Room Controllers DCV100 / DCV116 — Visual Domeless Room Controllers

## DESCRIPTION

The R4KPB11 is an emergency pushbutton station that provides the ability to place a unique call-in priority to the assigned console(s). The presence of a Cancel button allows for cancellation at the station. This type of station is normally located at a patient room head wall for placing a call for help, staff emergency and/or code call.

### ASSOCIATED EQUIPMENT

CLA222 / CLA244 — Audio Corridor Lights CLV122 / CLV144 — Visual Corridor Lights

Architect and Engineer (A&E) Specifications available online at: customerconnection.rauland.com Specifications subject to change without notice

©Copyright 2014 Rauland-Borg Corporation Printed in USA Rev 04/2014

800-752-7725905-607-2335

Fax 800-217-0977Fax 905-607-3554

