

MODEL: R4KPC10 — PULL CORD STATION



R4KPC10



FEATURES

- Plastic pull cord for easy activation
- Smooth, non-porous PVC coating on the cord provides an easily cleaned surface
- Call-Assurance LED
- Cancel touchpoint
- Continuous supervision for station presence
- Unique mounting plate design accommodates a variety of single and dual gang backboxes
- Plug-in connectors for easy service
- Water-resistant

SPECIFICATIONS

Power Required: 15V DC @ 2mA

Weight: 0.25 lb. (0.11 kg)

Size: W: 4.21" (10.69 cm)

H: 5.46" (13.87 cm)

D: 1.17" (2.97 cm)

Housing & Finish: High-impact molded ABS94VO
light gray faceplate and insert

Controls One (1) pull cord for call point
One (1) Call-Assurance LED
One (1) Cancel touchpoint

Terminations: Plug-on connectors

Backbox Options: Raco 561, Steel City 58371 3/4R or any other single gang backbox. Mounting plate allows for North American, South American, and European style single and dual gang backboxes

Certification: UL/C-UL 1069; CE.

DESCRIPTION

The R4KPC10 — Pull Cord Station is an emergency pull cord station that has the ability to place a unique call-in priority from a single station to the assigned console(s). The R4KPC10 is typically located in bathrooms near the toilet and in the shower. The membrane Cancel button allows for cancellation of the call at the station. Unit may utilize remote Cancel button(s) for ease of nurse call cancel when pull cord is mounted in an inaccessible location (e.g. ceiling).

To make the station water-resistant, the station perimeter is caulked on three sides with sealant. It also has water diversion channels that open along the bottom of the station for drainage.

The R4KPC10 is connected to its associated corridor light or domeless room controller and is continually supervised for station presence. Through programming, a "Trouble" message can annunciate at the associated console(s) when the station is removed from the system.

ASSOCIATED EQUIPMENT

CLA222 / CLA244 — Audio Corridor Lights

CLV122 / CLV144 — Visual Corridor Lights

DCA200 / DCA216 — Audio Domeless Room Controllers

DCV100 / DCV116 — Visual Domeless Room Controllers

*Architect and Engineer (A&E) Specifications available online at: customerconnection.rauland.com
Specifications subject to change without notice*

©Copyright 2014 Rauland-Borg Corporation Printed in USA Rev 04/2014