Responder® Health Care Communications Systems

MODEL: R4K11V — SINGLE PATIENT STATION







FEATURES

- · Over four (4) call-in priorities available
- DIN receptacle for patient nurse call and entertainment controls
- · Monitor LED with Cancel button
- · No dummy plugs required
- Continuous supervision for station presence
- · Plug-in connectors for easy service
- Unique mounting plate design accomodates a variety of single and dual gang backboxes



SPECIFICATIONS

Power Required: 15.5V DC @ 2mA

Weight: 0.15 lb. (0.07 kg) Size: W: 4.21" (10.69 cm) H: 5.46" (13.87 cm) D: 1.17" (2.97 cm)

Housing & Finish: High-impact molded ABS94VO;

light gray faceplate

Controls: One (1) DIN receptacle
One (1) Cancel button

One (1) Call-Assurance LED indicator

Terminations: Plug-on connectors

Backbox Options: Raco 561, Steel City 58371 3/4R or any other single gang backbox. Mounting

plate allows for North American, South American, and European style single

and dual gang backboxes

Certification: UL/C-UL 1069; CE.

DESCRIPTION

The R4K11V — Single Patient Station is a single bed station typically used in a visual system. The station allows both patients and staff to place different call-in priorities, depending on their requirements, to the assigned console(s). The bed station can interface with call cords and entertainment speakers to initiate calls and provide entertainment control.

The bedside station is connected to its associated corridor

light or domeless room controller and is continually supervised for station presence. Through programming, a "Station Out" call can annunciate at the associated console(s) when the station is removed from the system.

ASSOCIATED EQUIPMENT

CLV122 / CLV144 - Visual Corridor Lights

DCV100 / DCV116 - Visual Domeless Room Controllers

Pillow Speakers

CCDIN - Call Cord

Architect and Engineer (A&E) Specifications available online at: customerconnection.rauland.com Specifications subject to change without notice

©Copyright 2014 Rauland-Borg Corporation Printed in USA Rev 04/2014



• 800-752-7725

• 905-607-2335

Fax 800-217-0977Fax 905-607-3554

