

MODEL: 351200 - NURSE CONSOLE



FEATURES

- VoIP device
- Full-Duplex audio
- Color Display Screen
- Over 990 possible unique facility-defined call priorities
- Thirty-two (32) programmable functions
- 5-line display with associated function/scroll/select buttons
- Day/Night tones
- Console speaker level adjustment
- Optional tone mute of calls in progress
- Displays up to three (3) incoming calls with the ability to scroll to see additional pending calls
- Twelve (12) unique call-in tones
- Choice of instant 2-way communication with handset or push-to-talk operation via speaker-microphone
- Room swing capabilities
- Continuously supervised with self-diagnosing error messages and distinctive console failure audio alert

SPECIFICATIONS

DISPLAY: 5-line display on a color, 1/4 VGA screen
POWER REQUIREMENTS: PoE (802.3af compliant) 26-56VDC 9 watts
CONNECTION: 10/100 Mb Ethernet
WEIGHT: 2.65 lbs (6.7 kilograms) without carton or Ethernet cable
SIZE: W: 10.38" (26.4 CM)
H: 9.18" (23.3 CM)
D: 1.90" (4.8 CM)
HOUSING AND FINISH: High-impact molded Cyclopol 2950
UL 94-5VB; light gray faceplate

CONTROLS: Four (4) soft touch keys programmable for up to thirty-two functions; Three (3) line selector keys; One (1) scroll key for call selection; One (1) scroll key for function selection; One (1) standard ten (10) key dial pad; One (1) Push-to-Talk button; One (1) cancel button; One (1) volume control button
TERMINATIONS: Plug on connector.
CERTIFICATIONS: UL 1069, IEC/UL 60601-1, -1-2, FCC Part 15 (all pending)

DESCRIPTION

The VoIP Nurse Console is typically located at a local nursing station, work station, centralized communications center, or any place where staff receive calls, communicate with staff, or initiate any Responder 5 related features. The console may be desk or wall mounted. The VoIP Nurse Console provides complete information concerning incoming calls including: patient or staff member's room location, bed (if applicable), call priority, and length of time call has been waiting. An operator may selectively answer any of three (3) calls displayed or scroll through a list using the key pad for call selection. A call may be answered using the handset for semi-private conversation or the

Push-to-Talk key for a hands-free conversation. The VoIP Nurse Console can be configured for up to twenty-four (24) functions including Setting/Review Service Requirements, Emergency Call Upgrade, Day/Night tones, Staff Follow, Sequential Room Monitor, Swinging Groups of Rooms, etc. These functions are activated using the scroll key pad and selector buttons. Functions are customized on an individual basis allowing each VoIP Nurse Console to be programmed for its specific location and purpose. The VoIP Nurse Console is continually supervised for both power and signal.

Rauland-Borg Corporation

Architects and Engineers Specifications available on disc. Specifications subject to change without notice.

USA • 800-752-7725 • Fax 800-217-0977
CANADA • 905-607-2335 • Fax 905-607-3554
www.rauland.com

MODEL #351200
05/2008