

MODEL: 353001 - ENHANCED SINGLE PATIENT STATION



FEATURES

- Functions as single bed station with two (2) additional pushbuttons
- Multiple call-in priorities available
- Tilt/Release DIN receptacle for patient entertainment controls and handset intercom with entertainment muting during nurse call
- Tilt/Release DIN receptacle allows for ease of disconnecting handset from the patient station
- Auxiliary device receptacle with separate call-in priority setting
- No dummy plugs required
- Interfaces with specialty beds via separate receptacle and control module
- Interfaces with a remote Pillow Speaker via separate station LED to indicate specialty bed is connected
- LED to indicate remote Pillow Speaker activity
- Call-Assurance LED to indicate a call placed from the pillow speaker
- Call-Assurance LED to indicate a call placed from the ¼" receptacle
- Output for lighting control options direct to low voltage lighting controller
- Monitor LED for audio activity
- Cancel button for localized call cancellation
- Continuous supervision of station for loss of data and/or power faults
- Plug-in connectors for easy service
- Bio-seal options to cover buttons and allow for easy disinfecting of the station

SPECIFICATIONS

POWER REQUIRED: 300 mA at 18V

WEIGHT: 0.66 lb. (0.300 kg)

SIZE: W: 6.39" (16.22 cm)

H: 4.25" (10.80 cm)

D: 2.50" (6.35 cm), 0.56" (1.4 cm) off-wall

HOUSING & FINISH: High-impact molded Cylcoloy 2950 UL 94-5VB; light grey faceplate

CONTROLS: One (1) DIN receptacle, One (1) ¼" receptacle, One

(1) Cancel button, One (1) Monitor LED, Two (2) Call-assurance LED indicators, Two (2) Special Buttons with Call-Assurance, and Two (2) Special Bed LED indicators

TERMINATIONS: Plug-on connectors

BACKBOX REQUIREMENTS: 3 Device Non-gangable, 3-1/2" Deep (i.e. Raco 697), Steel City GW-335C, Steel City H3BD-3/4 with 3GC plaster ring, or UL recognized equivalent metal electrical box

CERTIFICATION: UL/C-UL 1069, FCC Part 15 Class B, IEC60601-1 and IEC60601-1-2 CE Mark (LVD) (all Pending)

DESCRIPTION

The Enhanced Single Patient Station is a single bed station with the added capability of placing two additional calls. The station also allows both patients and staff to place different call-ins, depending on their requirements, to the assigned nurse console(s), staff terminal(s), along with other annunciation devices such as wireless phones. The patient station interfaces with entertainment handsets and specialty beds to initiate calls, control entertainment, control lighting, and provide nurse call audio and entertainment audio through the respective speakers.

When used with the 350302 Feature Bed Control Module, the audio capabilities are transferred to the bed rail with entertainment muting. The patient station is connected to its associated corridor light or Domeless room controller and is continually supervised for both power and data.

Through programming, a message can annunciate at the associated console(s) and / or the remote status application if a problem occurs.

Rauland-Borg Corporation

Architects and Engineers Specifications available on disc. Specifications subject to change without notice.

USA • 800-752-7725 • Fax 847-679-4106
CANADA • 905-607-2335 • Fax 905-607-3554
www.rauland.com

MODEL #353001
05/2008