

MODEL: R5K SINGLE BUTTON STATION



R4KPB12



FEATURES

- Extra large back-lit button for easy activation
- Call-Assurance/Monitor LED
- Cancel button
- Plug-in connectors for easy service
- Continuous supervision of station
- Optional antimicrobial Bio-seal to cover buttons and allow for easy disinfecting of the station

SPECIFICATIONS

Power Required: 4mA @ 15VDC

Power Required when used with Speaker Module: 7mA @ 15VDC

Weight: 0.20 lbs. (0.09 kg)

Size: W: 3.2" (8.1 cm)

H: 4.25" (10.9 cm)

D: 0.6" (1.5 cm) in back box: 0.5" (1.3 cm) off-wall

Housing and Finish: High-impact molded Cyclooy 2950 UL 94-5VB; light grey faceplate

Controls: One (1) push button for call actuation, One (1) Call-assurance/Monitor LED, and One (1) Cancel button

Terminations: Plug-on connectors

Backbox Requirement: : 1-gang, Non-gangable [W: 2.25" (5.7 cm) H: 4" (10.2 cm) D: 3.5" (8.9 cm)]

Backbox Requirement when used with Speaker

Module: 3-gang, Non-gangable [W: 5.5" (14 cm) H: 3.75" (9.5 cm) D: 3.5" (8.9 cm)]

Certification: Designed for compliance to ANSI/UL 1069, IEC 60950, CE, RoHS / WEEE Compliant. Assembled in a U.S. FDA Registered facility.

DESCRIPTION

The Responder® 5000 Single Button Station is a call push-button station providing the ability to place a call for help. Pressing the Cancel button cancels the call. Using special buttons, the station can be customized for unique call priorities such as: "Staff Assist," "Bath," "Help," etc.

The Single Button station is connected to its associated corridor light and is continually supervised for station presence. Through programming, a "Trouble" message can annunciate at the associated console(s) when the station is removed from the system.